Heraeus

Technical Data Sheet



THICK FILM MATERIALS

Product Type: End Terminations

Product Name: ET1856







Solderable and Plateable Silver/ Palladium End Termination

Description

ET1856 is a Pb and Cd free solderable & nickel plateable silver/palladium (4:1) end termination designed to be compatible on Multilayer ceramic chip capacitors (NPO and X7R bodies). Nickel plating can be done without pre- plate processing due to the low glass content on the fired surface.

Key Benefits

- Nickel plateable no pre-plate processing
- Low usage excellent coverage uniformity
- Dense fired mircotructure
- Cu plateable
- Pb and Cd free
- REACH¹ and ROHS² compliant

Typical Properties

Viscosity

30 – 40 Kcps Brookfield RVT SC4 – 14 spindle, 6R utility cup at 10 rpm, 25 °C

Solids

76.5 ± 1.5 %

Solderability

Sn62/Pb36/Ag2 at 230 °C 5 second dip, RMA flux

Sn6/Pb40 at 250 °C, 5 second dip, RMA flux

FOG

 $\leq 10~\mu m$ (at 4^{th} scratch)

Recommended Processing Guidelines

Drving

150 °C for 10 minutes 20 minute total cycle time

Firing

650 – 800 °C peak temperature Dwell time at temp. 5 – 7 minutes

Thinner:

RV-372

Warranty:

Material guaranteed to meet specifications for 6 months from date of shipment.

Storage:

Store in a dry location at 5-25 °C.

DO NOT REFRIGERATE.

Allow paste to come to room temperature prior to opening. Spatulate well before using, as settling may occur during storage.



Technical Data Sheet







Solderable and Plateable Silver/ Palladium End Termination

Legend:

- ¹⁾ REACH compliant according to the <u>latest</u> * Annex XIV to Regulation (EC) of the European Parliament and of the council on the Registration, Evaluation, Authorisation and Restriction of Chemicals ("REACH") by European Chemicals Agency and its subsequent amendments; the <u>material does not contain any substance listed in Annex XIV.</u>
- 2) RoHS compliant according to the <u>latest</u> * Directives (European Union) of Restriction of Hazardous Substances ("RoHS") and its subsequent amendments (including the exceptions related to Pb)

Heraeus Electronics

Heraeus Deutschland GmbH & Co. KG Heraeusstraße 12 – 14 63450 Hanau, Germany www.heraeus-electronics.com Americae

Phone +1 610 825 6050 electronics.americas@heraeus.com

Asia Pacific

Phone +65 6571 7677 electronics.apac@heraeus.com China

Phone +86 21 3357 5457 electronics.china@heraeus.com

Europe, Middle East and Africa

Phone +49 6181 35 3069, +49 6181 35 3627 electronics.emea@heraeus.com