

Technical Data Sheet

THICK FILM MATERIALS

Product Type: Component Metallization

Product Name: PCC11889



Lead Free Silver Conductor

Description

PCC11889 is a Pb and Cd free low temperature firing silver paste designed to screen print solderable electrodes onto a variety of electronic ceramic component. The fired film forms a highly adherent bond to many types of substrates, including piezoelectric transducers (PZTs), NTC thermistors, alumina, steatite, and porcelain. The metalized electrode is readily solderable for external lead attachment.

Key Benefits

- REACH¹ and ROHS² compliant
- Pb and Cd free
- Lower firing temperature (< 700 °C)
- Designed for piezoelectric transducers (PZTs), NTC thermistors, alumina, steatite, and porcelain.

Typical Properties

Resistivity

≤ 3.0 mΩ/□
at 25 μm fired film thickness

Adhesion

Sn62/Pb36/Ag2 at 200 °C
0.10 in x 0.10 in pads
Initial ≥ 6.6 lbs

Solderability

Sn62/Pb36/Ag2, 230 °C
2 – 3 seconds dip
Excellent

Viscosity

100 – 120 Kcps, Brookfield HBT
CP-51 spindle at 1 rpm, 25 °C

Solids (typical)

> 70 %

Recommended Processing Guidelines

Printing

60 – 200 stainless steel mesh screen
0.7 – 1.0 mil emulsion

Drying

150 °C for 10 – 15 minutes

Firing

Optimum firing parameters depend on substrate composition
550 – 700 °C peak firing temperature
Dwell time of 8 – 12 minutes
Total cycle time of 45 – 60 minutes
Larger parts may require a longer firing profile

Thickness

Fired 10 – 14 μm

Thinner

RV-252

Warranty

Material guaranteed to meet specifications for 6 months from date of shipment.

Storage

Store in a dry location at 5 – 25 °C.

DO NOT REFRIGERATE.

Allow paste to come to room temperature prior to opening. Spatulate well before using, as settling may occur during storage.

Technical Data Sheet



Lead Free Silver Conductor

Legend:

1) REACH compliant according to the latest ** Annex XIV to Regulation (EC) of the European Parliament and of the council on the Registration, Evaluation, Authorisation and Restriction of Chemicals ("REACH") by European Chemicals Agency and its subsequent amendments; the material does not contain any substance listed in Annex XIV.

2) RoHS compliant according to the latest ** Directives (European Union) of Restriction of Hazardous Substances ("RoHS") and its subsequent amendments (including the exceptions related to Pb).

* See the data sheet issue date (DD/MM/YY) as reference of validity of latest edition which is available on request

Heraeus Electronics
Heraeus Deutschland GmbH & Co. KG
Heraeusstraße 12 – 14
63450 Hanau, Germany
www.heraeus-electronics.com

Americas
Phone +1 610 825 6050
electronics.americas@heraeus.com

China
Phone +86 21 3357 5457
electronics.china@heraeus.com

Asia Pacific
Phone +65 6571 7677
electronics.apac@heraeus.com

Europe, Middle East and Africa
Phone +49 6181 35 3069, +49 6181 35 3627
electronics.emea@heraeus.com