



TO 92, Housed Platinum Temperature Sensor according to DIN EN 60751

Temperature range -50 °C to +150 °C

The PRTD in a plastic housing is characterized by its standardized signal according to DIN EN 60751 (according to IEC 751), interchangeability, excellent long-time stability and accuracy. It offers an optimal price-performance ratio in large volume applications including HVAC and industrial equipment.

Nominal Resistance R_0	Tolerance	Order Number	Packaging
100 Ohm at 0 °C	F 0.3 (Class B)	32 209 210	VCI-plastic bag
1000 Ohm at 0 °C	F 0.3 (Class B)	32 209 220	VCI-plastic bag

Temperature and tolerance range

Tolerance class F 0.3 (B): -50 °C to +150 °C

Continuous operation

Temperature coefficient

TCR = 3850 ppm/K

Response time

Water current ($v= 0.4\text{m/s}$):
 $t_{0.5} = 0.7 \text{ s}$
 $t_{0.9} = 2.0 \text{ s}$

Air stream ($v= 2\text{m/s}$):
 $t_{0.5} = 8.0 \text{ s}$
 $t_{0.9} = 26.0 \text{ s}$

Measuring current

100 Ω : 0.3 to 1.0 mA
 1000 Ω : 0.1 to 0.3 mA
 (self-heating has to be considered)

Long-term stability

R_0 -Drift 0.06 % after 1000 hours at 150 °C

Self-heating


Pt100: 0.4 K/mW at 0 °C
 Pt1000: 0.2 K/mW at 0 °C

Specific volume resistance

20 °C: $5 \times 10^{16} \Omega\text{cm}$
 150 °C: $5 \times 10^{13} \Omega\text{cm}$


Physical data of housing

Material: duroplastic
 Coefficient of thermal expansion: $13 \times 10^{-6} \Omega/^\circ\text{C}$
 Thermal conductivity: 0.65 W/mK
 Moisture absorption: 0.5 % (P.C.T.: 121 °C, 24 hours)



The information provided in this data sheet describes certain technical characteristics of the product, but shall not be qualified or construed as quality guarantee (Beschaffenheitsgarantie) in the meaning of sections 443 and 444 German Civil Code. The information provided in this data sheet regarding measurement values (including, but not limited to, response time, long-term stability, vibration and shock resistance, insulation resistance and self-heating) are average values that have been obtained under laboratory conditions in tests of large numbers of the product. Product results or measurements achieved by customer or any other person in any production, test, or other environment may vary depending on the specific conditions of use. The customer is solely responsible to determine whether the product is suited for the customer's intended use; in this respect Heraeus cannot assume any liability. The sale of any products by Heraeus is exclusively subject to the General Terms of Sale and Delivery of Heraeus in their current version at the time of purchase, which is available under www.heraeus.com/gtc or may be furnished upon request. This data sheet is subject to changes without prior notice.

Heraeus Nexensos GmbH, Reinhard-Heraeus-Ring 23, 63801 Kleinostheim, Germany
 Web: www.heraeus-nexensos.com



TO 92, Housed Platinum Temperature Sensor according to DIN EN 60751

Temperature range -50 °C to +150 °C

Flammability

UL94-V0

Soldering connection

Cu alloy Sn/Pb coating

Length (LL)

12.5 mm ± 0.5 mm

Connection technology

Suitable for soft soldering

Packaging

Alternative packaging forms on request.

Storage life

9 months (in original packaging)

Nitrogen atmosphere recommended

Note

Other tolerances, values of resistance and wire lengths are available on request.

California Proposition 65



WARNING:

This product can expose you to chemicals including carbon black, which is known to the State of California to cause cancer. For more information go to www.p65warnings.ca.gov.



The information provided in this data sheet describes certain technical characteristics of the product, but shall not be qualified or construed as quality guarantee (Beschaffenheitsgarantie) in the meaning of sections 443 and 444 German Civil Code. The information provided in this data sheet regarding measurement values (including, but not limited to, response time, long-term stability, vibration and shock resistance, insulation resistance and self-heating) are average values that have been obtained under laboratory conditions in tests of large numbers of the product. Product results or measurements achieved by customer or any other person in any production, test, or other environment may vary depending on the specific conditions of use. The customer is solely responsible to determine whether the product is suited for the customer's intended use; in this respect Heraeus cannot assume any liability. The sale of any products by Heraeus is exclusively subject to the General Terms of Sale and Delivery of Heraeus in their current version at the time of purchase, which is available under www.heraeus.com/gtc or may be furnished upon request. This data sheet is subject to changes without prior notice.

Heraeus Nexensos GmbH, Reinhard-Heraeus-Ring 23, 63801 Kleinostheim, Germany

Web: www.heraeus-nexensos.com